



High Performance Adhesive Caulk

Lil' Caulk, LLC

High Performance Siliconized Acrylic Latex

Lil' Caulk Siliconized Acrylic Latex is a high performance, paintable sealant used for sealing interior and exterior joints. Lil' Caulk Siliconized Acrylic Latex cures to form a strong, flexible water tight seal. Lil' Caulk is further modified with proprietary additives to optimize resistance to oxidation, UV degradation and cold temperatures. Lil' Caulk will also expand and contract with paint which allows it to be painted using most latex and oil based paints.

COMMON APPLICATIONS: Lil' Caulk Siliconized Acrylic Latex is an excellent sealant for many Commercial, Industrial and Construction applications. Such applications include: Bathroom Installation/Sealing, Window and Door Interior Sealing, General Sealing, General Construction, Portable Housing Interior Applications, Countertops, Trim work, Tub and Tile, Cabinets & Applications where Painting is Required, Etc. Can be used

for additional applications not listed. Lil' Caulk recommends testing prior to use.

COMMON BONDING SUBSTRATES: Lil' Caulk can be used on a variety of substrates. Please inquire or test your substrates before use. Substrates may vary with manufacturer. We have listed some common substrates: Ceramics, Glass, Granite, Marble, Some Metals, Most Woods, Some Plastics, Porcelain, Porous Surfaces (Concrete, Brick, Etc.) Can be used on additional substrates not listed. Lil' Caulk recommends testing prior to use.

DIRECTIONS: 1) Surface should be clean and dry. 2) Remove cap and cut off the tip of the nozzle at a 45 degree angle to the required bead size. 3) Dispense by squeezing the tube. 4) Apply as needed. If tooling is required do so within the first 15 minutes. Sealant will skin in approximately 30 minutes (dependent on temperature & humidity). 5) **Allow the adhesive to cure completely. Strength will start to develop immediately and continue increasing for 7-14 days until fully cured.** 6) Wet adhesive can be cleaned with warm water. Dry sealant can be removed by abrading or scraping. Suggested temperatures for application are 40°F to 90°F. Lil' Caulk has a service temperature of -20°F to 180°F.

LIMITATIONS: Do not store at elevated temperatures. Use only on clean surfaces free of contaminants. Cold temperature and high humidity will slow curing (40°F and below will be most significant). Lil' Caulk does not recommend using when temperatures are below 40°F. If you are unsure about your specific paint, test before application. Allow treated wood & asphalt to cure 6 months before application. Allow new concrete to cure 30 days before applying sealant. Do not use in applications below waterline.

Lil' Caulk will pass 5 freeze thaw cycles without harm of product. Prevention of continual freezing and thawing is required to maintain quality. For more information please view our product data sheet and safety data sheet on our website: www.lilcaulk.com

PRODUCT WARRANTY: Lil' Caulk shall in no event be liable for incidental or consequential damages. Except as expressly stipulated, Lil' Caulk's liability, expressed or implied, is limited to the stated selling price of any defective goods. Lil' Caulk recommends that the product is tested thoroughly in each application before use. Warning: May be harmful if swallowed. Causes mild skin irritation. Causes eye irritation. May cause long lasting harmful effects to aquatic life.

Precautionary Statements: Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Store in a dry, cool place. Protect from freezing. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. For additional information, consult SDS for this product.

First Aid: Eye Contact: Flush eyes with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation develops and persists: Get medical advice/attention. Ingestion: Do not induce vomiting, unless directed by medical personnel. Get immediate medical attention if symptoms occur. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Skin Contact: Wash with plenty of soap and water while removing all contaminated clothes and shoes. If irritation persists: Get medical attention. Wash contaminated clothing before use. Inhalation: Remove to fresh air. If breathing is difficult,

leave area to obtain fresh air. If breathing remains difficult, get medical attention.

VOC CATEGORY: SEALANT OR CAULKING COMPOUND, VOC Limit < 3%. KEEP OUT OF REACH OF CHILDREN. INFO TRAC # 1-800-535-5053.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

